LONGEST LIFE - HIGHEST PERFORMANCE





DEKA POWR MATE BATTERIES combine all the benefits of a maintenance-free gel battery with an on-board, capacity-matched charger. No need to return the pallet jack to a remote, centralized charging area; simply connect the **DEKA POWR MATE** charger into any 15-amp 120-volt AC outlet.

Innovative Design Features:

- 2 battery sizes to fit virtually any pallet jack for light to medium use
- Protective hinged cover standard on all DEKA POWR MATE BATTERIES
- Secure-fit battery hold-downs
- Integrated connector and auto start/stop charger with LED display
- Batteries completely serviceable without removing unit from equipment

The **DEKA POWR MATE**...maximum power, ease of operation and two to three times longer battery life than similar units supplied with group 24 and 27 AGM batteries.

RECHARGE GUIDE:

ESTIMATED HOURS OF OPERATION	APPROX. HOURS To recharge				
1	1.00 - 1.50				
2	2.50 - 3.00				
3	4.00 - 4.50				
4	4.50 - 5.50				
5	5.50 – 7.50				
6	7.00 - 8.50				

ISO 9001 ISO/TS 16949 ISO 14001





SPECIFICATIONS:

PART NUMBER	BATTERY Model	A.H. CAPACITY 6 Hr. Rate	K.W.H. CAP. 6 HR. RATE	A.C. Supply	DIMENSIONS (INCHES)			APPROX.
					LENGTH	WIDTH	HEIGHT	WEIGHT (lbs.)
3800	8GGC2 - 24 Volts	155 A.H. to 1.70 VPC	3.60	120 Volts	25½	8%6	24½	350
3801	8GGC2 - 24 Volts	155 A.H. to 1.70 VPC	3.60	120 Volts	25½	7 ½	24½	350

"POWERED FOR PERFORMANCE"®

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212

Order Department Hotline: 610-682-3260

www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

E.P.M. Form No. 0718 Rev. 12/07 © 2007 by EPM Printed in U.S.A. **DISTRIBUTED BY:**